



Be Right™



EVITA OXY System Paket 3 (NL)

Artikel-Nr.:

085G4003.56.001

VERALTETER ARTIKEL

Dieser Artikel ist nicht mehr verfügbar.

Maintenance-free dissolved

oxygen measurement: EVITA OXY

The package provides low maintenance dissolved oxygen measurement (under one hour maintenance a year). The spherical form and the fins support easy self-cleaning of the transmitter and the sensor. The transmitter converts the measurements of the rep

TILTCAL automatic calibration

Easily replaceable sensor no regeneration!

Self-cleaning design

High accuracy and noise immunity

Connectable directly to PLC

Technische Daten

Ansprechzeit: 22 s OXY 1100 - 50 µm

Bemerkungen: Composition:

EVITA OXY 4100 transmitter (ball), 0-5 mg/l, 10 m cable

EVITA OXY 1100 sensor, 50 µm

mounting bracket for EVITA OXY

Betriebsbedingungen: 0 - 50 °C (Sensor)

Betriebstemperaturbereich: -40 - 60 °C (Transmitter)

Diaphragma: Measurement between anode and a terminal in contact with the measured medium

Durchmesser: 240 mm

Gehäuse-Schutzklasse: IEC 529: IP 68 (10 m); NEMA 6P (30')

Genauigkeit: ± 0.1 % of FSO at calibrating temperature

Gewicht: 2,7 kg

Kabellänge: 10 m Two-wire, screened cable 2 x 0.75 mm² (18 AWG) cable

Kommunikation: HART communication superposed on current output

Lagerbedingungen:	0 °C - 70 °C
Material:	PBT/PC
Messbereich:	0 - 5 mg/L can be configured
Messprinzip:	Clark cell
Probentemperatur:	0 - 40 °C (32 - 104 °F)
Spannungsversorgung (Volt):	12 - 30 V DC
Stromausgang:	3.80 to 24 mA
Verzögerungszeit:	10 - 300 s (default 40 s)