



## Digitales Gateway, konvertierbar, PVDF

Artikel-Nr.: D3726E2T.99

CHF Preis: Kontakt

Kein Versanddatum angezeigt

The low-maintenance design eliminates polarization or coating electrodes problems connected with electrode-type conductivity sensors. A built-in Pt1000 thermometer compensates for in process temperature changes. The measuring principle is based on induction.

### Wide Measuring Range

Hach's Inductive Conductivity Sensors measure 200 up to 2,000,000 microSiemens/cm. A built-in Pt 1000 RTD compensates the measured conductivity for changes in process temperature.

### Low Maintenance Design

The inductive sensor design eliminates polarization and electrode coating problems that commonly affect conventional contacting electrode-type conductivity sensors.

### Versatile Mounting Styles

Sensors can be installed using a choice of four mounting styles—immersion, insertion, union, and sanitary.

### Principal of Operation

Inductive conductivity sensors induce a low current in a closed loop of solution, then measure the magnitude of this current to determine the solution's conductivity. The conductivity analyzer drives Toroid A, inducing an alternating current in the solution. This current signal flows in a closed loop through the sensor bore and surrounding solution. Toroid B senses the magnitude of the induced current which is proportional to the conductance of the solution. The analyzer processes this signal and displays the corresponding reading.

### Withstands Harsh Environments

The inductive sensor is available in sanitary (CIP) flange style and convertible styles in PFA®, polypropylene, PEEK®, and PVDF material. Select sensors can withstand high pressures and temperatures.

---

## Technische Daten

Bemerkungen:	Composed of 3726E2T analogue sensor with 6 m fixed cable, AD digital gateway and 1 m digital cable.
Betriebsbedingungen:	-10 - 120 °C (Sensor)
Druckbereich:	6,9 bar bei 120 °C
Durchfluss:	max. 3 m/s
Eintauchtiefe:	79.2 mm
Gewährleistung:	24 Monate
Inhalt:	Enthält: Sensor mit 6 m (20 ft) Kabel und Handbuch
Kabellänge:	6 m
Länge:	127 mm

Material:	Sensor Body: PVDF
Messbereich:	200 µS/cm - 2000 mS/cm
Sensor-Anschluss:	0.75" NPT outer thread
Temperatur-Sensor:	Pt1000 RTD

---

## Inhalt

Enthält: Sensor mit 6 m (20 ft) Kabel und Handbuch