

HQ40D BSB System HQ40d mit IntelliCal BSB Set, Stand

Artikel-Nr.: **HQ40D.99.701000**

VERALTETER ARTIKEL
Dieser Artikel ist nicht mehr verfügbar.

Rugged portable meters for use in the field and plant.

Portables 2-Kanal Multimeter für die Messung von pH, Redox, Leitfähigkeit, Sauerstoff (LDO) und ISE. Basis-Gerät mit BSB Set und Stand

The digital meter/electrode system combines reliability, flexibility and ease of use. Interchangeable INTELLICAL electrodes are recognised automatically and store all relevant data. Rugged, nearly indestructible outdoor versions with multiple cable lengths enable measurements even at previously inaccessible locations.

Measurement performance certified according to MCERTs regulation

Replaced by NEW HQ Series.

Herausragende Sicherheit und besonders einfache Handhabung

Vielseitige Elektroden für alle Einsatzbereiche, z. B. Abwasser, Trinkwasser, Prozesswasser

Zuverlässige Ergebnisse von unzugänglichen Einsatzorten und über

große Distanzen – auch für pH

Zuverlässige O_2-Ergebnisse – ohne Kalibrierung oder Elektrolytwechsel

Vollständiges GLP Datenmanagement

Technische Daten

Art der Messung:	QC Lab
Datenexport:	Download via USB connection to PC or flash memory device. Automatically transfer entire data log or as readings are taken. Power supply adapter required.
Eingänge:	2
Elektroden-Typ:	Intellical Digital SMART Standard Laboratory or Rugged Field
Gewährleistung:	36 Monate
Inhalt:	Meter package includes HQ40D Portable Meter; 4 AA batteries; Power adapter, USB/DC power adapter for data transfer; quick-start guide and user manual; HQD Meter Stand; Borosilicate glass BOD Bottles & ground glass stoppers, 300 mL, 6/pk.Intellical LBOD101 Luminescent Dissolved Oxygen (LDO) sensor for BOD measurement, DO Cap with its iButton (already mounted), Test certificate, and Basic User Manual.

Inhalte:	No
Kit?:	Ja
Leitfähigkeit Auflösung:	0.01 µS/cm with 2 digits
Modell:	HQ40D – Multi/2 Channels
Needed Cable Length:	1
Parameter:	pH, mV, ISE, DO, Conductivity, TDS, Salinity, Resistivity, ORP, Temp
Parameters:	BOD
	NA
	NA
PC Datenübertragungssoftware :	HQD Series Meter Data Transfer Utility
Sensor A:	LBOD10101 (1 m)
Sensor B:	NA
Sensor C:	NA
Sensoren enthalten?:	None
Sensors:	Sensor A: LBOD10101
	Sensor B: NA
	Sensor C:
Umgebungsbedingungen Temperatur:	0 - 60 °C (32 - 140 °F)

Inhalt

Meter package includes HQ40D Portable Meter; 4 AA batteries; Power adapter, USB/DC power adapter for data transfer; quick-start guide and user manual; HQD Meter Stand; Borosilicate glass BOD Bottles & ground glass stoppers, 300 mL, 6/pk.Intellical LBOD101 Luminescent Dissolved Oxygen (LDO) sensor for BOD measurement, DO Cap with its iButton (already mounted), Test certificate, and Basic User Manual.